

Modern Digital Multimeters		
PR-61D		
Specification	Range	Best Accuracy
Model		PR-61D
DC Voltage (V)	60mV/600mV/6V/60V/600V/1000V 220mV/2.2V/22V/220V/1000V	±(0.5%+1)
AC Voltage (V)	60mV/600mV/6V/60V/600V/750V 220mV/2.2V/22V/220V/750V	±(1.0%+3)
DC Current (A)	600μA/6000μA/60mA/600mA/6A/10A 200μA/2200μA/22mA/220mA/2.2A/10A	±(1.0%+3)
AC Current (A)	600μA/6000μA/60mA/600mA/6A/10A 200μA/2200μA/22mA/220mA/2.2A/10A	±(1.2%+5)
Resistance (Ω)	600Ω/6KΩ/60KΩ/600KΩ/6MΩ/60MΩ 220Ω/2.2KΩ/22KΩ/220KΩ/2.2MΩ/22MΩ/ 220MΩ	±(1.0%+2)
Capacitance (F)	40nF/400nF/4μF/40μF/400μF/4000μF 22nF/220nF/2.2μF/22μF/220μF/2.2mF/22 mF/220mF	±(3.0%+5)
Frequency (Hz)	10Hz-10MHz 10Hz-220MHz	±(0.1%+4)
Temperature (°C)	-40°C ~ 1000°C	
Temperature (°F)	-40°F ~ 1832°F	
Features		
Display Count		6000
Auto Range		✓
True RMS		✓
Bandwidth (Hz)		45Hz ~ 3kHz
Duty Cycle	0.1% ~ 99.9%	✓
Diode		✓
Auto Power Off	Around 15 Minutes	
Continuity Buzzer		✓
Low Battery Indication	≤7.5V	✓
Data Hold		✓
Relative Mode		✓
MAX/MIN		✓
Peak Value		
RS-232		✓
LCD Backlight		✓
Analogue Bar Graph		61
Input Protection		✓
Input Impedance for DCV	Around 10MΩ	✓
General Characteristic		
Power	9V Battery (6F22)	
LCD Size	65mm X 43 mm	
Product Color	Red and Grey	
Product Net Weight	370g	
Product Size	180mm X 87mm X 47 mm	
Standard Accessories	PR- 61D-Battery, Test Lead,Multi-Purpose Socket,RS-232 Interface Cable,PC Software CD	
Standard Individual Packing	Gift Box, English Manual	
Standard Quantity Per Carton	20 PCs	
Standard Carton Measurement	465mm X 335mm X 345mm	
Standard Carton Gross Weight	12 Kg	
Optional Accessories		
USB Interface Cable		